

=====I. PRODUCT IDENTIFICATION=====

Trade Name: Fast 50 Contract Grade Adhesive

Chemical names, common names: Synthetic latex/resin blend

Manufacturer's Name: Capitol USA  
Address: 300 Cross Plains Blvd.  
Dalton, GA 30720

Emergency Phone: 800/831-8381  
Business Phone: 706/277-6241

Date prepared: 01/21/09  
By: M. King

HMIS Rating: H = 1 F = 0 R = 0

=====II. HAZARDOUS INGREDIENTS=====

	<u>CAS No.</u>	<u>% by wt.</u>	<u>PEL</u>	<u>TLV</u>
Mineral Spirits	8052-41-3	1.8%	100 ppm	100 ppm
Methanol	67-56-1	1.5%	200 ppm	200 ppm

Reportable hazardous chemicals for SARA TITLE III Section 311, 312, 313:

Methanol

=====III. PHYSICAL PROPERTIES =====

Vapor Density (Air=1): Greater than 1  
Solubility in Water: Miscible  
Vapor Pressure (mmHg at 20c): Same as water  
Evaporation rate (nBuAc=1): Same as water  
Boiling Point: 212F  
Specific gravity: 1.16  
pH: 9.4 - 9.9

Appearance & odor: Light tan/cream mastic with a mild odor.

Percent Volatile: 51 - 53% by weight (water)

VOC calculated:(Coating) 50 grams/liter.

=====IV. FIRE AND EXPLOSION=====

Flash point, Pensky-Martens C.C: NA  
Auto-Ignition Temperature, F: NA  
Flammable limits in air, Volume %: Lower: Not Applicable Upper: NA  
Fire Extinguishing Materials:

Water Spray       Carbon Dioxide       Other:  
 Foam       Dry Chemical

Special Fire fighting Procedures: Wear self-contained breathing apparatus.

Unusual Fire and Explosion Hazards: None known

=====

===== V. HEALTH HAZARD INFORMATION =====

SYMPTOMS OF OVEREXPOSURE

Inhalation: May cause slight irritation to upper respiratory tract.  
Eyes: May cause slight irritation.  
Skin: None known; may cause slight irritation.  
Ingestion: Not a likely route of entry under proper handling conditions.  
May cause vomiting. Symptoms may be the same as inhalation.

-----  
HEALTH EFFECTS OR RISKS FROM EXPOSURE

Acute: May cause mild skin irritation, irritation of respiratory tract.  
Chronic: None known.

-----  
FIRST AID: EMERGENCY PROCEDURES

Eye contact: Flush with water for at least 15 minutes. If irritation persists, seek medical attention.  
Skin contact: Wash with soap and water. If irritation persists, see a physician.  
Inhalation: Remove to fresh air, administer oxygen and if necessary, seek medical attention.  
Ingestion: Not a likely route of entry under proper handling conditions. Seek medical attention if necessary.

-----  
SUSPECTED CANCER AGENT?

NO:  X

YES: \_\_\_\_\_ Federal OSHA      \_\_\_\_\_ NTP      \_\_\_\_\_ IARC      \_\_\_\_\_ Cal/OSHA

-----  
MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE: None Known

=====VI. REACTIVITY DATA=====

Stability:   X   Stable        Unstable

Conditions to Avoid: Protect from freezing.

Incompatibility (Materials to Avoid): Oxidizing materials

Hazardous Decomposition Products (including combustion products):  
Oxides of carbon, water and organic compounds of unknown structure.

Hazardous Polymerization: Does not occur

Conditions to Avoid: None known.

Corrosive to Metal: No                      Oxidizer: No

=====VII. SPECIAL HANDLING INFORMATION=====

Ventilation and Engineering Controls: Use local exhaust. Do not use closed air circulating system. Open windows and doors, if necessary.

Respiratory Protection: Normally none required. Use product in a well ventilated area. Use NIOSH approved respirator if irritation to respiratory tract. If vapors or mists are generated, wear NIOSH/MSHA approved organic vapor/mist respirator.

Eye Protection: Chemical goggles or face shield. Gloves: Chemical resistant gloves.

Other clothing and Equipment: If clothing becomes contaminated, remove and clean before re-wearing.

Work Practices, Hygienic Practices: Follow all label instructions.

Protective Measures During Maintenance of Contaminated Equipment:

Use goggles and gloves when cleaning adhesive from equipment.  
Maintain proper ventilation.

=====**VIII. SPILL, LEAK, AND DISPOSAL PROCEDURES**=====

Keep out of sewer systems to prevent blockage due to polymer deposits. Soak up material with absorbent material (sand, sawdust) and place into closed containers for disposal.

*Note: Dispose of all wastes in accordance with Federal, State and Local regulations.*

=====**IX. Storage & Handling DATA**=====

Other Handling and Storage requirements: Protect against physical damage. Store in a cool, dry place (50F - 90F). Keep away from excessive heat. Protect from freezing.

=====**X. Regulatory Information** =====

Hazardous Waste 40CFR261: NO Hazardous Waste Number:

Hazardous Substance Superfund: NO RQ(lbs):

All components are in TSCA inventory.

=====**XI. SHIPPING DATA**=====

D.O.T. Proper Shipping Name (49CFR172.101-102): None.

Hazardous Substance (49CFR CERCLA list): No. RQ: N/A

D.O.T. Hazard Classification (49CFR 172.101-102):  
Primary: None Secondary: None.

D.O.T. Labels Required (49CFR172.101-102): None.

D.O.T. Placards Required (CFR172.504): None.

Poison Constituent (49CFR172.203(K)): None.

Bill of Lading Description: Adhesive, NOS

UN/NA Code: N/A

Capitol USA believes the data set forth herein are accurate as of the date hereof, and makes no warranty with respect thereto and expressly disclaims all liability for reliance thereon. Such data are offered solely for your consideration, investigation and verification.