

MATERIAL SAFETY DATA SHEET
TA480 THIN SPREAD VINYL COMPOSITION TILE ADHESIVE

02/18/09

SECTION I - PRODUCT IDENTIFICATION

MANUFACTURER'S NAME: Roberts Capitol/QEP

ADDRESS: 300 Cross Plains Blvd., PO Box 2023, Dalton, GA 30722

TELEPHONE #: 706-277-5294

GENERIC ID: Latex Based Flooring Adhesive

PRODUCT IDENTITY: TA480 Thin Spread VCT Adhesive

EMERGENCY PHONE: 706-277-5294

DOT HAZARD CLASSIFICATION: None

SECTION II - HAZARDOUS COMPONENTS

NONE PER OSHA REGULATION: 29CFR1910.1200. None per SARA Title III, Section 313 and TSCA 40 CRF 372

SECTION III - PHYSICAL DATA

INITIAL BOILING POINT: 212°F.

VAPOR DENSITY (AIR=1.0): Same as water

G/L VOC (CALCULATED): 0.00

VAPOR PRESSURE: Same as water

SPECIFIC GRAVITY: 1.09

PERCENT VOLATILES: 47.3%

SECTION IV - FIRE AND EXPLOSION DATA

FLASH POINT: NA

EXTINGUISHING MEDIA: NA

SPECIAL FIRE FIGHTING PROCEDURES: None

UNUSUAL FIRE & EXPLOSION HAZARDS: None

EXPLOSIVE LIMIT (PRODUCT): NA

HAZARDOUS DECOMPOSITION PRODUCTS: None

SECTION V - HEALTH HAZARD DATA

PERMISSIBLE EXPOSURE LEVEL: NA

EFFECTS OF EXPOSURE: EYES- Possible mild irritation. SKIN- None known. BREATHING- None known.

THRESHOLD LIMIT VALUE: NA

SECTION VI - REACTIVITY DATA

STABILITY: Stable

HAZARDOUS DECOMPOSITION: None

CONDITIONS TO AVOID: None Known

INCOMPATIBILITY: None

HAZARDOUS POLYMERIZATION: None

SECTION VII - SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Absorb liquid on paper, vermiculite, floor absorbent, or other absorbent material. Solidified materials accepted for landfill disposal in most locations. Check all local, state, and federal regulations.

SECTION VIII - PROTECTIVE EQUIPMENT

VENTILATION: Open all available windows and entrances to insure good ventilation.

RESPIRATOR PROTECTION: None needed

PROTECTIVE GLOVES: None needed

EYE PROTECTION: Wear glasses or protective goggles to avoid splashes.

OTHER PROTECTIVE EQUIPMENT: None required. Wash Hands Thoroughly with Soap and Water.

SECTION IX - SPECIAL PRECAUTIONS

Protect from freezing. Use only in applications as stated on the label. Do not take internally. Close container after each use. Avoid skin and eye contact.

Ventilation with fresh air, including open doors and windows should be observed during any flooring installation. Operate HVAC systems at 100% fresh air intake before, during and after installation to eliminate lingering odors or particulate matter.
KEEP OUT OF REACH OF CHILDREN

Capitol USA believes the data sets forth herein are accurate as of the date hereof, and makes no warranty with respect thereto and expressly disclaims all liability for reliance thereon. Such data are offered solely for your consideration, investigation and verification.