

=====I. PRODUCT IDENTIFICATION=====

Trade Name: Woody 060 (High Performance Acrylic/Urethane Wood Adhesive)

Chemical names, common names: Acrylic/Urethane Copolymer/Resin Dispersion

Manufacturer's Name: Roberts Capitol, Inc.  
Address: 300 Cross Plains Blvd.  
Dalton, GA 30720

Emergency Phone: 706-277-5294  
Business Phone: 706-277-5294

Date prepared: 05/12/2010  
By: M. King

HMIS Rating: H = 1 F = 0 R = 0

=====II. HAZARDOUS INGREDIENTS=====

None

Reportable hazardous chemicals for SARA TITLE III Section 311, 312, 313:

None

=====III. PHYSICAL PROPERTIES =====

Vapor Density (Air=1): Greater than 1 Boiling Point: 212F  
Solubility in Water: Miscible Specific gravity: 1.34  
Vapor Pressure (mmHg at 20c): Same as water pH: 8.5 - 9.5  
Evaporation rate (nBuAc=1): Same as water  
Appearance & odor: Light tan mastic; slight acrylic odor.

Percent Volatile: 17-19% by weight  
VOC calculated: VOC: 16 grams/liter (Coating).

=====IV. FIRE AND EXPLOSION=====

Flash point, Pensky-Martens C.C: NA  
Auto-Ignition Temperature, F: NA  
Flammable limits in air, Volume %: Lower: Not Applicable Upper: NA  
Fire Extinguishing Materials:

- Water Spray       Carbon Dioxide       Other:
- Foam       Dry Chemical

Special Firefighting Procedures: Wear self-contained breathing apparatus.

Unusual Fire and Explosion Hazards: None known

=====

===== **V. HEALTH HAZARD INFORMATION** =====

SYMPTOMS OF OVEREXPOSURE

Inhalation: May cause slight irritation to upper respiratory tract.

Eyes: May cause slight irritation.

Skin: May cause slight irritation.

Ingestion: Not a likely route of entry under proper handling conditions.  
May cause vomiting. Symptoms may be the same as inhalation.

-----  
HEALTH EFFECTS OR RISKS FROM EXPOSURE

Acute: May cause mild skin irritation, irritation of respiratory tract.

Chronic: None known.  
-----

FIRST AID: EMERGENCY PROCEDURES

Eye contact: Flush with water for at least 15 minutes. If irritation persists, seek medical attention.

Skin contact: Wash with soap and water. If irritation persists, see a physician.

Inhalation: Remove to fresh air, administer oxygen and if necessary, seek medical attention.

Ingestion: Not a likely route of entry under proper handling conditions. Seek medical attention if necessary.  
-----

SUSPECTED CANCER AGENT?

NO: X

YES: \_\_\_\_\_ Federal OSHA      \_\_\_\_\_ NTP      \_\_\_\_\_ IARC      \_\_\_\_\_ Cal/OSHA



=====**VIII. SPILL, LEAK, AND DISPOSAL PROCEDURES**=====

Keep out of sewer systems to prevent blockage due to polymer deposits. Soak up material with absorbent material (sand, sawdust) and place into closed containers for disposal.

*Note: Dispose of all wastes in accordance with Federal, State and Local regulations.*

=====**IX. Storage & Handling DATA**=====

Other Handling and Storage requirements: Protect against physical damage. Store in a cool, dry place (50F - 90F). Keep away from excessive heat. Protect from freezing.

=====**X. Regulatory Information** =====

Hazardous Waste 40CFR261: NO Hazardous Waste Number:

Hazardous Substance Superfund: NO RQ(lbs):

All components are in TSCA inventory.

=====**XI. SHIPPING DATA**=====

D.O.T. Proper Shipping Name (49CFR172.101-102): Adhesive.

Hazardous Substance (49CFR CERCLA list): No. RQ: N/A

D.O.T. Hazard Classification (49CFR 172.101-102):  
Primary: None Secondary: None.

D.O.T. Labels Required (49CFR172.101-102): None.

D.O.T. Placards Required (CFR172.504): None.

Poison Constituent (49CFR172.203(K)): None.

Bill of Lading Description: Adhesive, NOS

UN/NA Code: N/A

Roberts believes the data set forth herein are accurate as of the date hereof, and makes no warranty with respect thereto and expressly disclaims all liability for reliance thereon. Such data are offered solely for your consideration, investigation and verification.