



product *Specification*

#033

Fast Setting Seam Adhesive



033 Fast Setting Seam Adhesive is a solvent based, nonflammable, high strength seam adhesive designed specifically for the seaming of commercial and residential carpets. 033 is extremely suitable for use with all carpet types except solid vinyl back carpet products. 033 is simple and easy to use. It's unique, sag resistant formulation keeps the adhesive high on the edge of the carpet that makes for a more uniform and strong bond.

033 is ideal for sealing and seaming indoor/outdoor commercial or residential carpets. It is also perfect for glue down or double-glue down carpet installations. 033's fast setting property also makes it the product of choice when installing patterned carpet. 033's fast dry time locks the carpet in place and reduces the tendency to slip.

Open Time: 0 minutes

Working Time: 30 minutes

Use to Seam:

Carpet: Jute • Urethane • ActionBac® • Latex Unitary • Woven • Hot Melt backed

INSTRUCTIONS FOR USE

1. Condition adhesive and materials to 65°F and 35%-65% relative humidity, 48 hours prior to and after installation.
2. Remove inner seal before using.
3. Pour 033 from metal container into plastic squeeze bottle.
4. Apply an 1/8" bead of adhesive using plastic squeeze bottle equipped with dispenser tip at carpet primary backing and immediately butt opposite cut.
5. Roll immediately thereafter with carpet tractor.

6. Clean up wet adhesive immediately with white cloth and mineral spirits or safety solvent (011)

WARNING: VAPOR HARMFUL • HARMFUL OR FATAL IF SWALLOWED • CONTAINS METHYLENE CHLORIDE • Use only in well ventilated areas • Open all windows and doors or use other means to insure continuous introduction and movement of fresh air • Do not use in basements or other poorly ventilated areas • Wear a NIOSH approved self contained breathing apparatus or other approved supplied air respiratory protection device if use conditions generate vapors in excess of recommended exposure limits • Keep container closed when not in use • Avoid skin or eye contact • Keep away from heat or flame as toxic gases may be formed • KEEP AWAY FROM CHILDREN

In case skin contact, wash with soap and water. In case of eye contact, wash with copious amounts of water for 15 minutes and contact physician immediately. Inhalation: Remove to fresh air immediately. If breathing stops, administer artificial respiration. In case of ingestion, do not induce vomiting. Contact physician immediately or Regional Poison Control Center.



Capitol USA, LLC
300 Cross Plains Blvd. • PO Box 2023
Dalton, GA 30722
800-831-8381 • Fax: 706-277-5753
Jim Walker ProSeries TechLine 888-234-8400
Website www.capitolusa.com