

Capitol™ product **Specification**

FAST 19

High Performance Outdoor Carpet Adhesive



FAST 019 High Performance Outdoor Carpet Adhesive is Capitol USA's best bet for the installation of outdoor carpet. FAST 019's flammable, solvent based formula works in the most aggressive environments.

- High Ultimate Bond Strengths
- Fast Setup and Dry Time
- Early Weather Resistant
- Easy to Trowel
- Water Proof

Description: FAST 019 High Performance Outdoor Carpet Adhesive

Flammability: Extremely Flammable

Open Time: 15 minutes

Working Time: 30 minutes

Clean Up: Clean wet adhesive and tools with white cloth and mineral spirits.

Shelf Life: One year in closed container.

Limitations: Freeze / Thaw stable. For exterior use only.

Packaging: • 3.5 Gallon • 1 Gallon

For The Installation Of:

- ActionBac®/Jute • Latex Unitary • Waffle Backed • Rubber Backed

For Use Over:

- Concrete • Exterior Grade Plywood • Aged asphalt paving (hot applied) • Fiberglass (abraded) • Terrazzo

Instructions For Use:

1. Condition room and materials at 65°F for 48 hours prior to, during and after installation. Avoid hot, sunny, windy and rainy conditions.
2. Clean substrate to remove any dirt or debris prior to installation.
3. Make sure substrate is free from grease, oil, paint, or other contaminant that might interfere with the bond of the adhesive.
4. Do not install on floors with high moisture or alkali content.
5. Spread adhesive with the appropriate trowel. Ensure 100% coverage
6. Allow the adhesive to flash for 15 minutes prior to installing the flooring material.
7. Apply only as much adhesive that can be installed within 30 minutes.
8. Press flooring firmly into adhesive.
9. Roll in both directions according to floor manufacturers recommendations.
10. Clean wet adhesive and tools with white cloth and mineral spirits.
11. Protect from water 24 hours after installation.

Caution:

DANGER: EXTREMELY FLAMMABLE • Keep away from heat, sparks, and open flame • Do not smoke, extinguish all flames and pilot lights, and turn off stoves, heaters, electric motors, and other sources of ignition during use and until all vapors are gone. Close container after each use. Avoid contact with skin and eyes. **KEEP OUT OF REACH OF CHILDREN.**

This product contains a substance known to the State of California to cause reproductive harm.

Trowel Requirements



13 - 14 square feet /gallon

- ActionBac® / Jute Backed
- Latex Backed Carpets
- Waffle Backed Carpets
- Rubber Backed

