




product Specification

FAST 024 Non-Flammable Outdoor Carpet Adhesive



FAST 024 Outdoor Carpet Adhesive is the perfect adhesive to install outdoor carpet in areas where safety and performance are of critical concern.

sum Cement Underlayment • VCT • Felt Backed Vinyl Sheet Goods (prime with an acrylic sealer, such as Capitol's LL400 Liquid Latex) • Do not use over existing cutback

- High Ultimate Bond Strengths
- Water Resistant When Dry
- Longer Working Time
- Non-Flammable
- Easy to Trowel

Description: FAST 024 Non-Flammable Outdoor Carpet Adhesive

Flammability: Non-Flammable

Open Time: 15 minutes

Working Time: 30 minutes

Clean Up: Clean wet adhesive and tools with white cloth and soap and water.

Shelf Life: One year in closed container.

Limitations: Do not subject to temperatures below 10°F. If frozen, warm to at least 70°F for 24 hours and stir before using.

Packaging:

- 4 Gallon • 1 Gallon • 1 Quart

For The Installation Of:

- ActionBac®/Jute • Latex Unitary • Waffle Backed • Rubber Backed • Urethane • Marine Backed



For Use Over:

- Concrete • Plywood • APA Grade Particle Board • OSB • Terrazzo • Hardwood Floors • Latex-Portland Cement Underlayment • Gyp

Instructions For Use:

1. Condition room and materials at 65°F for 48 hours prior to, during and after installation. Avoid hot and sunny conditions.
2. Sweep floor and remove any dirt or debris prior to installation.
3. Make sure floor is free from grease, oil, paint, or other contaminant that might interfere with the bond of the adhesive.
4. Do not install on floors with high moisture or alkali content.
5. Spread adhesive with the correct trowel making sure to maintain trowel notchings throughout the installation.
6. Allow the adhesive to flash for 15 minutes prior to installing the flooring material.
7. Apply only as much adhesive that can be installed within 30 minutes.
8. Press flooring firmly into adhesive.
9. Roll in both directions according to floor manufacturers recommendations.
10. Protect from rain or water exposure for 48-72 hours after installation.
11. Clean wet adhesive and tools with white cloth and soap and water.

Caution:

Avoid contact with skin and eyes. If splashed in eyes, flush with copious amounts of water for 15 minutes and call physician. Wash skin thoroughly with soap and water. Use with positive fresh air cross-ventilation. Do not take internally. If swallowed do not induce vomiting, call physician immediately. Keep container closed. KEEP OUT OF REACH OF CHILDREN

