



product Specification

Fast 400 Ultra Premium Carpet Adhesive



FAST 400 Ultra Premium Carpet Adhesive delivers every time for super fast tack, strong early leg development and high ultimate bond strengths. FAST 400 is ideal for the installation of stiff and boardy carpet products, for high-end carpets or for installations that are exposed to a high amount of traffic.

- Very Fast Tack for Difficult to Install Carpet
- Fast Early Legs to Hold Down Even the Stiffest Carpets
- Very High Bond Strengths for High Traffic Areas
- Ideal for Double Glue Installations

Description: Fast 400 Ultra Premium Carpet Adhesive

Flammability: Non-Flammable

Open Time: 0-15 minutes (For non-porous backings, allow full 15 minute open time.)

Working Time: 45 minutes

Clean Up: Clean wet adhesive and tools with white cloth and soap and water. Mineral spirits when dry.

Shelf Life: One year in closed container.

Limitations: Do not subject to temperatures below 10°F. If frozen, warm to at least 70°F and stir before using. For interior use only.

Packaging: 4 Gallon

For The Installation Of:

- Jute Backed Carpet • Urethane • ActionBac® Carpet
- Latex Unitary Carpet • Woven • Hot Melt Backed Carpet • Double Glue Installations • Felt-backed vinyl sheet goods.

For Use Over:

- Concrete • Plywood • APA Grade Particle Board • OSB • Terrazzo • Hardwood Floors • Latex-Portland Cement Underlayment • Gypsum Cement Underlayment • VCT • Felt Backed Vinyl Sheet Goods (prime with an acrylic sealer, such as Capitol's LL400 Liquid Latex) • Do not use over existing cutback

Instructions For Use:

1. Condition room and materials at 65°F for 48 hours prior to, during and after installation. Avoid hot and sunny conditions.
2. Sweep floor and remove any dirt or debris prior to installation.
3. Make sure floor is free from grease, oil, paint, or other contaminant that might interfere with the bond of the adhesive.
4. Do not install on floors with high moisture or alkali content.
5. Spread adhesive with the correct trowel making sure to maintain trowel notchings throughout the installation.
6. Allow the adhesive to flash for 15 minutes prior to installing the flooring material.
7. Apply only as much adhesive that can be installed within 45 minutes.
8. Press flooring firmly into adhesive.
9. Roll in both directions according to floor manufacturers recommendations.
10. Clean wet adhesive and tools with white cloth and soap and water.

Caution:

Avoid contact with skin and eyes. If splashed in eyes, flush with copious amounts of water for 15 minutes and call physician. Wash skin thoroughly with soap and water. Use with positive fresh air cross-ventilation. Do not take internally. If swallowed do not induce vomiting, call physician immediately. Keep container closed. **KEEP OUT OF REACH OF CHILDREN**



Trowel Requirements	
<p>1/8 x 1/8 x 1/16 "V"</p> <p>13-14 square yards /gallon</p> <ul style="list-style-type: none"> • ActionBac® / Jute • Urethane (attached cushion) • Hot Melt 	<p>1/8 x 1/8 x 1/8</p> <p>8-9 square yards /gallon</p> <ul style="list-style-type: none"> • Latex Unitary • Urethane Unitary • Woven
<p>1/16 x 1/16 x 1/16</p> <p>18-19 square yards /gallon</p> <ul style="list-style-type: none"> • Pad to Floor (Double Glue) 	<p>1/8 x 1/8 x 1/16</p> <p>6-7 square yards / gallon</p> <ul style="list-style-type: none"> • Double Glue Installations (Carpet to Pad)

Capitol USA, LLC
 300 Cross Plains Blvd. • PO Box 2023
 Dalton, GA 30722
 800-831-8381 • Fax: 706-277-5753
 Jim Walker ProSeries TechLine 888-234-8400
 Website www.capitolusa.com