



product

SAF T BOND Series  
Process Patent #5,258,425

# Specification

## MP 002

### High Performance Multi Purpose Flooring Adhesive



MP 002 is our most popular multipurpose flooring adhesive. Designed with performance and economy in mind.

- Excellent Working Time for Carpet or Vinyl
- Non-Staining for Felt-Backed Vinyl Sheet Goods
- Strong Early Grab
- High Bond Strengths

□

**Description:** MP002 High Performance Multi Purpose Flooring Adhesive

**Flammability:** Non-Flammable

**Open Time:** 15 minutes □

**Working Time:** 45-60 Minutes

**Clean Up:** Water when wet; Safety solvent or mineral spirits when dry.

**Shelf Life:** One year in closed container.

**Limitations:** Do not subject to temperatures below 10°F. If frozen, warm to at least 70°F for 24 hours and stir before using. For interior use only.

**Packaging:** 4 Gallon • 1 Gallon

□

**For The Installation Of:**

- Jute Backed Carpet • Urethane • ActionBac® Carpet
- Latex Unitary Carpet • Woven • Hot Melt Backed Carpet • Felt-backed Sheet Vinyl □

**For Use Over:**

- Concrete • Plywood • APA Grade Particle Board
- OSB • Terrazzo • Hardwood Floors • Latex-Port

land Cement Underlayment • Gypsum Cement Underlayment • VCT • Felt Backed Vinyl Sheet Goods (prime with an acrylic sealer, such as Capitol's LL400 Liquid Latex) • Do not use over existing cutback

**Instructions For Use:**

1. Condition room and materials at 65°F for 48 hours prior to, during and after installation. Avoid hot and sunny conditions.
2. Sweep floor and remove any dirt or debris prior to installation.
3. Make sure floor is free from grease, oil, paint, or other contaminant that might interfere with the bond of the adhesive.
4. Do not install on floors with high moisture or alkali content.
5. Spread adhesive with the correct trowel making sure to maintain trowel notchings throughout the installation.
6. Allow the adhesive to flash for 15 minutes prior to installing the flooring material.
7. Apply only as much adhesive that can be installed within 45 minutes.
8. Press flooring firmly into adhesive.
9. Roll in both directions according to floor manufacturers recommendations.
10. Clean wet adhesive and tools with white cloth and soap and water.

**Caution:**

Avoid contact with skin and eyes. If splashed in eyes, flush with copious amounts of water for 15 minutes and call physician. Wash skin thoroughly with soap and water. Use with positive fresh air cross-ventilation. Do not take internally. If swallowed do not induce vomiting, call physician immediately. Keep container closed. KEEP OUT OF REACH OF CHILDREN

**Trowel Requirements**

<p style="text-align: center;"><b>1/8 x 1/8 x 1/16 "V"</b></p> <p>13-14 square yards /gallon • ActionBac® / Jute • Urethane (attached cushion) • Hot Melt</p>	<p style="text-align: center;"><b>1/8 x 1/8 x 1/8</b></p> <p>8-9 square yards /gallon • Latex Unitary • Urethane Unitary • Woven</p>
<p style="text-align: center;"><b>1/16 x 1/16 x 1/16</b></p> <p>18-19 square yards /gallon • Felt Back Vinyl Sheet • Pad to Floor (double glue)</p>	<p style="text-align: center;"><b>1/8 x 1/8 x 1/16</b></p> <p>6-7 square yards / gallon • Double Glue Installations (carpet to pad)</p>
<p style="text-align: center;"><b>3/32 x 3/32 x 3/32 "V"</b></p> <p>17-18 square yards /gallon • Jute • Low Density Urethane</p>	



Capitol USA, LLC  
300 Cross Plains Blvd. • PO Box 2023  
Dalton, GA 30722  
800-831-8381 • Fax: 706-277-5753  
Jim Walker ProSeries TechLine 888-234-8400  
Website [www.capitolusa.com](http://www.capitolusa.com)