

# Specification

## MP 003

### Contract Grade Multi Purpose Flooring Adhesive



MP003 is the installer's choice for price and performance.

- Longer Working Time for Carpet or Vinyl
- Non-Staining for Felt-Backed Vinyl Sheet Goods
- Strong Early Grab
- Easy to Trowel

#### Instructions For Use:

1. Condition room and materials at 65°F for 48 hours prior to, during and after installation.
2. Sweep floor and remove any dirt or debris prior to installation.
3. Make sure floor is free from grease, oil, paint, or other contaminant that might interfere with the bond of the adhesive.
4. Do not install on floors with high moisture or alkali content.
5. Spread adhesive with the appropriate trowel making sure to maintain trowel notchings throughout the installation.
6. Allow the adhesive to flash for 15 minutes prior to installing the flooring material.
7. Apply only as much adhesive that can be installed within 45 minutes.
8. Press flooring firmly into adhesive.
9. Roll in both directions according to floor manufacturers recommendations.
10. Clean wet adhesive and tools with white cloth and soap and water.

**Description:** MP 003 Contract Grade Multi Purpose Flooring Adhesive

**Flammability:** Non-Flammable

**Open Time:** 15 minutes

**Working Time:** 45-60 Minutes

**Shelf Life:** One year in closed container.

**Limitations:** For interior use only.

Protect from Freezing

**Packaging:** 4 Gallon • 1 Gallon • 1 Quart

#### For The Installation Of:

- Jute Backed Carpet • Urethane • ActionBac® Carpet
- Light Latex Unitary Carpet • Felt-backed Sheet Vinyl

#### For Use Over:

- Concrete • APA approved Plywood • Underlayment Grade Particle Board • OSB • Terrazzo • Hardwood Floors • Latex-Portland Cement Underlayment
- Gypsum Cement Underlayment • VCT

#### Trowel Requirements



18-19 square yards /gallon  
• Felt Back Vinyl sheet



17-18 square yards /gallon  
• Jute  
• Low Density Urethane



13-14 square yards /gallon  
• ActionBac® / Jute



8-9 square yards /gallon  
• Light Latex Unitary

