

Specification

PS 100

Trowel Grade Pressure Sensitive Adhesive



PS 100 Trowel Grade Pressure Sensitive Adhesive installs the widest range of flooring types and as such is our best multipurpose flooring adhesive.

- Installs the Broadest Range of Flooring Materials
- Can be Used for Either Permanent or Releasable Applications
- Permanently Pressure Sensitive

- Extended Working Time
- Easy to Trowel

Description: PS 100 Trowel Grade Pressure Sensitive Adhesive

Flammability: Non-Flammable

Open Time: 15 minutes (Permanent Bond)/60 Minutes (Releasable Bond)

Working Time: 24 hours

Clean Up: Clean wet adhesive and tools with white cloth and soap and water.

Shelf Life: One year in closed container.

Limitations: Do not subject to temperatures below 10°F. If frozen, warm to at least 70°F and stir before using.

Packaging: 4 Gallon • 1 Gallon • 1 Quart

For The Installation Of:

- Carpet & Carpet Tile • Solid Vinyl Sheet & Tile • Felt Back Vinyl Sheet Flooring • Rubber Tile • Synthetic Carpet Pad

For Use Over:

- Concrete • Plywood • APA Grade Particle Board • OSB • Terrazzo • Hardwood Floors • Latex-Portland Cement Underlayment • Gypsum Cement Underlay




ment • VCT • Felt Backed Vinyl Sheet Goods (prime with an acrylic sealer, such as Capitol's LL400 Liquid Latex) • Do not use over existing cutback

Instructions For Use:

1. Condition room and materials at 65°F for 48 hours prior to, during and after installation. Avoid hot and sunny conditions.
2. Sweep floor and remove any dirt or debris prior to installation.
3. Make sure floor is free from grease, oil, paint, or other contaminant that might interfere with the bond of the adhesive.
4. Do not install on floors with high moisture or alkali content.
5. Spread adhesive with the correct trowel making sure to maintain trowel notchings throughout the installation.
6. Allow the adhesive to flash for the appropriate amount of time depending on the type of bond required prior to installing the flooring material.
7. Apply only as much adhesive that can be installed within 24 hours.
8. Press flooring firmly into adhesive.
9. Roll in both directions according to floor manufacturers recommendations.
10. Clean wet adhesive and tools with white cloth and soap and water.

Caution:

Avoid contact with skin and eyes. If splashed in eyes, flush with copious amounts of water for 15 minutes and call physician. Wash skin thoroughly with soap and water. Use with positive fresh air cross-ventilation. Do not take internally. If swallowed do not induce vomiting, call physician immediately. Keep container closed. KEEP OUT OF REACH OF CHILDREN

Trowel Requirements	
 3/32 x 3/32 x 3/32 "V" 17-18 square yards /gallon • Jute • Low Density Urethane	 1/8 x 1/8 x 1/16 "V" 13-14 square yards /gallon • ActionBac® / Jute • Urethane (attached cushion)
 1/16 x 1/16 x 1/16 18-19 square yards /gallon • Felt Back Vinyl sheet • VCT • Solid Vinyl Sheet Goods (not shrink to fit)	
• Carpet Tile • Solid Vinyl Tile (12"x12" max.) • Rubber Tile (12"x12" max.) • Pad to Floor (Double Glue)	

