



product

SAFT BOND Series  
Process Patent #5,258,425

# Specification

## PS 200

### Spray Grade Pressure Sensitive Adhesive



PS200 Spray Grade Pressure Sensitive Adhesive is a lower viscosity product, ideal for spraying or applying with roller. PS200 is an acrylic-latex product making suitable for almost all flooring types.

- Installs the Broadest Range of Flooring Materials
- Can be Used for Either Permanent or Releasable Applications

- Low viscosity, Easy to Spray
- Permanently Pressure Sensitive
- Extended Working Time

**Description:** PS200 Spray Grade Pressure Sensitive Adhesive

**Coverage:** 25-35 yds. (225-315 sq. ft.) per gallon

**Flammability:** Non-Flammable

**Open Time:** 15 minutes (Permanent Bond)/60 Minutes (Releasable Bond)

**Working Time:** 24 hours

**Clean Up:** Clean wet adhesive and tools with white cloth and soap and water.

**Shelf Life:** One year in closed container.



**Limitations:** Do not subject to temperatures below 10°F. If frozen, warm to at least 70°F for 24 hours and stir before using.

**Packaging:** 5 Gallon Pail • 4 Gallon Pail

**For The Installation Of:**

- Carpet & Carpet Tile
- Solid Vinyl Sheet (not perimeter bonded) & Tile
- Felt Back Vinyl Sheet Flooring
- Rubber Tile
- Synthetic Carpet Pad

**Application Requirements**

1/4" Nap Roller     621-625 Spray Tip  
25-30 yds/gallon   30-35 yds/gallon  
225-270 sq. ft./gallon   270-315 sq. ft./gallon

**For Use Over:**

- Concrete
- Plywood
- APA Grade Particle Board
- OSB
- Terrazzo
- Hardwood Floors
- Latex-Portland Cement Underlayment
- Gypsum Cement Underlayment
- VCT
- Felt Backed Vinyl Sheet Goods (prime with an acrylic sealer, such as Capitol's LL400 Liquid Latex)
- Do not use over existing cutback

**Instructions For Use:**

1. Condition room and materials at 65°F for 48 hours prior to, during and after installation. Avoid hot and sunny conditions.
2. Sweep floor and remove any dirt or debris prior to installation.
3. Make sure floor is free from grease, oil, paint, or other contaminant that might interfere with the bond of the adhesive.
4. Do not install on floors with high moisture or alkali content.
5. Apply adhesive evenly on floor using either 1/4" nap roller or spray system.
6. Allow the adhesive to flash for the appropriate amount of time depending on the type of bond required prior to installing the flooring material.
7. Apply only as much adhesive that can be installed within 24 hours.
8. Press flooring firmly into adhesive.
9. Roll in both directions according to floor manufacturer's recommendations.
10. Clean wet adhesive and tools with white cloth and soap and water.

**Caution:**

Avoid contact with skin and eyes. If splashed in eyes, flush with copious amounts of water for 15 minutes and call physician. Wash skin thoroughly with soap and water. Use with positive fresh air cross-ventilation. Do not take internally. If swallowed do not induce vomiting, call physician immediately. Keep container closed. **KEEP OUT OF REACH OF CHILDREN**



Capitol USA, LLC  
 300 Cross Plains Blvd. • PO Box 2023  
 Dalton, GA 30722  
 800-831-8381 • Fax: 706-277-5753  
 Jim Walker ProSeries TechLine 888-234-8400  
 Website [www.capitolusa.com](http://www.capitolusa.com)