



product



# Specification

## VA300

### Solid Vinyl Sheet Flooring Adhesive



VA 300 Solid Vinyl Sheet Flooring Adhesive is the perfect answer for installing homogeneous vinyl flooring.

- Sets up Quickly
- Plasticizer Resistant
- Strong Permanent Bond
- Low Odor

**Description:** VA300 Solid Vinyl Sheet Flooring Adhesive

**Flammability:** Non-Flammable

**Open Time:** 15 - 30 minutes

**Working Time:** 45 minutes

**Clean Up:** Clean wet adhesive and tools with white cloth and soap and water.

**Shelf Life:** One year in closed container.

**Limitations:** Do not subject to temperatures below 10°F. If frozen, warm to at least 70°F for 24 hours and stir before using. For interior use only.

**Packaging:**

- 4 Gallon • 1 Gallon

**For The Installation Of:**

- Solid Vinyl Sheet & Tile • Vinyl Backed Broadloom Carpet • Rubber Tile • Carpet Tile

**For Use Over:**

- Concrete • Plywood • APA Grade Particle Board • OSB • Terrazzo • Hardwood Floors • Latex-Portland Cement Underlayment • Gypsum or Cement Under

layment • Do not use over existing cutback or non-porous substrates.



**Instructions For Use:**

1. Condition room and materials at 65°F for 48 hours prior to, during and after installation. Avoid hot and sunny conditions.
2. Sweep floor and remove any dirt or debris prior to installation.
3. Make sure floor is free from grease, oil, paint, or other contaminant that might interfere with the bond of the adhesive.
4. Do not install on floors with high moisture or alkali content.
5. Spread adhesive with the correct trowel making sure to maintain trowel notchings throughout the installation.
6. Allow the adhesive to flash for 15 minutes prior to installing the flooring material.
7. Apply only as much adhesive that can be installed within 1 hour.
8. Press flooring firmly into adhesive.
9. Roll in both directions according to floor manufacturers recommendations.
10. Clean wet adhesive and tools with white cloth and soap and water.

**Caution:**

Avoid contact with skin and eyes. If splashed in eyes, flush with copious amounts of water for 15 minutes and call physician. Wash skin thoroughly with soap and water. Use with positive fresh air cross-ventilation. Do not take internally. If swallowed do not induce vomiting, call physician immediately. Keep container closed. KEEP OUT OF REACH OF CHILDREN

**Trowel Requirements**

 <p><b>1/16 x 1/16 x 1/16</b></p> <p>18-19 square yards /gallon 160-170 square feet /gallon</p> <ul style="list-style-type: none"> <li>• Solid Vinyl Sheet Goods (no shrink to fit)</li> <li>• Solid Vinyl Tile (12"x12" max.)</li> <li>• Carpet tile (permanent)</li> <li>• Rubber Tile (12"x12" max.)</li> </ul>	 <p><b>3/32 x 3/32 x 3/32 "V"</b></p> <p>17-18 square yards /gallon</p> <ul style="list-style-type: none"> <li>• PVC Backed Broadloom Carpet</li> </ul>
---	--



Capitol USA, LLC  
300 Cross Plains Blvd. • PO Box 2023  
Dalton, GA 30722  
800-831-8381 • Fax: 706-277-5753  
Jim Walker ProSeries TechLine 888-234-8400  
Website [www.capitolusa.com](http://www.capitolusa.com)