



product



Specification

TA480

Thin Spread Vinyl Composition Tile Adhesive



TA 480 Thin Spread Vinyl Composition Tile Adhesive is our power performer for VCT installations. TA 480's unique formula makes it suitable for use over old cut back adhesive residue.

- Translucent Formula so Chalk Lines Remain Visible

Description: TA 480 Thin Spread Vinyl Composition Tile Adhesive

Flammability: Non-Flammable

Open Time: 45 minutes

Working Time: 24 hours

Clean Up: Clean wet adhesive and tools with white cloth and soap and water.

Shelf Life: One year in closed container.

Limitations: Do not subject to temperatures below 10°F. If frozen, warm to at least 70°F for 24 hours and stir before using.

Packaging:

- 4 Gallon • 1 Gallon • 1 Quart

For The Installation Of:

- Vinyl Composition Tile

For Use Over:

- Concrete • Plywood • APA Grade Particle Board • OSB • Terrazzo • Hardwood Floors • Latex-Portland Cement Underlayment • Gypsum or Cement Underlayment, existing VCT or Felt Backed Vinyl Sheet Goods must be primed with an acrylic sealer, such as Capitol's LL400 Liquid Latex.

Trowel Requirements

1/16 x 1/16 x 1/16
 18-19 square yards /gallon
 160-170 square feet /gallon
 • VCT (Vinyl Composition Tile)



Instructions For Use:

1. Condition room and materials at 65°F for 48 hours prior to, during and after installation. Avoid hot and sunny conditions.
2. Sweep floor and remove any dirt or debris prior to installation.
3. Make sure floor is free from grease, oil, paint, or other contaminant that might interfere with the bond of the adhesive.
4. Do not install on floors with high moisture or alkali content.
5. Spread adhesive with the correct trowel making sure to maintain trowel notchings throughout the installation.
6. Allow the adhesive to flash for 45 minutes or until dry to touch prior to installing the flooring.
7. Apply only as much adhesive that can be installed within 24 hours.
8. Press flooring firmly into adhesive.
9. Roll in both directions according to floor manufacturers recommendations.
10. Clean wet adhesive and tools with white cloth and soap and water.

Caution:

Avoid contact with skin and eyes. If splashed in eyes, flush with copious amounts of water for 15 minutes and call physician. Wash skin thoroughly with soap and water. Use with positive fresh air cross-ventilation. Do not take internally. If swallowed do not induce vomiting, call physician immediately. Keep container closed. KEEP OUT OF REACH OF CHILDREN



Capitol USA, LLC
300 Cross Plains Blvd. • PO Box 2023
Dalton, GA 30722

800-831-8381 • Fax: 706-277-5753

Jim Walker ProSeries TechLine 888-234-8400

Website www.capitolusa.com