



product

Specification

EAGLE PREMIUM MULTI-PURPOSE FLOORING ADHESIVE



EAGLE Premium Multipurpose Flooring Adhesive has been specifically designed to meet the demands of heavy commercial floor installation.

- Superior Bond Strength for High Traffic Areas

- Excellent Working Time for Carpet or Felt-Backed Vinyl Sheet Goods
- Perfect for Double Glue Installations
- Non-Staining for Felt-Backed Vinyl Sheet Goods

Open Time: 0-15 minutes

Working Time: 45-60 minutes at 72°F and 65% R.H.

Shelf Life: One year in closed container.

Flammability: Non-Flammable

Freeze Thaw Stability: 5 cycles at 10°F

Limitations: For interior use only. Protect from freezing. Do not use for vinyl backed products.

Packaging: 4 Gallon Pails

For The Installation of:

- Jute, Urethane, ActionBac®, Latex Unitary, Woven and Hot Melt Carpet Backings
- Felt-Backed Vinyl Sheet Goods.

Not Recommended for: Solid vinyl sheet, vinyl tile or vinyl backed carpet.

For Use Over:

- Concrete • ACCUPLY • APA Approved Grade Plywood
- Underlayment Grade Particle Board • OSB
- Terrazzo • Latex-Portland Cement Underlayment
- Primed Gypsum Underlayments

Instructions For Use:

1. Condition room and materials at 65°F for 48 hours prior to, during and after installation. Avoid hot and sunny conditions.
2. Sweep floor and remove any dirt or debris prior to installation.
3. Make sure floor is free from grease, oil, paint, or other contaminant that might interfere with the bond of the adhesive.
4. Do not install on floors with high moisture or alkali content.
5. Spread adhesive with the appropriate trowel making sure to maintain trowel notchings throughout the installation.
6. Allow the adhesive to flash for 15 minutes prior to installing the flooring material.
7. Apply only as much adhesive that can be installed within 45 minutes.
8. Press flooring firmly into adhesive.
9. Roll in both directions according to floor manufacturers recommendations.
10. Clean wet adhesive and tools with white cloth and soap and water.

Trowel Requirements

1/16 x 1/16 x 1/16

- 18-19 square yards /gallon
- Pad to Floor (double glue)

3/32 x 3/32 x 3/32

- 17-18 square yards /gallon
- Jute
- Low Density Urethane

1/8 x 1/8 x 1/16


- 6-7 square yards /gallon
- Double Glue Installations (carpet to pad)

1/8 x 1/8 x 1/8

- 8-9 square yards /gallon
- Latex Unitary
- Urethane Unitary
- Woven

1/8 x 1/8 x 1/16

- 13-14 square yards /gallon
- ActionBac® / Jute
- Urethane (attached cushion)
- Hot Melt



Roberts Capitol, Inc.
Boca Raton, FL 33487
www.capitoladhesives.com