



product *Specification*

TackBond Construction Adhesive



TackBond Construction Adhesive is a very fast drying gun grade construction adhesive available in 30-ounce tubes only. TackBond's fast drying performance makes it the ideal product for the installation of tackstrip on concrete surfaces. No longer will you have to pre-drill endless holes for concrete nails. Simply run out a 1/4" bead of TackBond on the floor, place the strip into the adhesive, pull strip back out to flash the adhesive for a minimum of 5 minutes,

re-insert tackstrip and let dry for 4-6 hours. TackBond's rapid bond development will then allow full power stretching without coming loose from floor.

TackBond Construction Adhesive is the perfect choice for tackstrip installation and many other construction related applications including the installation of reducer strips and thresholds, stair treads, metal moldings and trim, raised metal floor pedestals, ceramic tile fixtures and repairs.

Description: Tack Strip Adhesive

Polymer Base: Synthetic rubber

Solvents: Toluene, Hexane, and Acetone

Flammability: Extremely flammable (F.P. <0° F TCC)

Coverage: One 30.5oz. tube will install approximately 80-120 lineal feet of tackstrip depending on width of strip.

Clean Up: Mineral spirits, use caution for flammability of solvent

Shelf Life: One year in closed container

Packaging: 30.5 oz. cartridges (12/case)

For Use With:

- Tack Strip
- Reducer Strips and Thresholds
- Stair Treads
- Metal Moldings
- Trim

- Raised Metal Floor Pedstals
- Ceramic Fixtures and Tile Repairs
- General Construction Use

Application: All surfaces to be bonded must be clean and dry. Apply bead (cut nozzle to desired size) to all surfaces to make contact. If placing sheet over studs, bead each stud. If applying paneling over old walls, bead edges of panel and "zigzag" bead through center. Sheet should be pressed in immediately and nailed. Bond should develop within 20-30 minutes of placement.

CAUTION: EXTREMELY FLAMMABLE. Harmful or fatal if swallowed. Vapors Harmful. Avoid use near fire or spark. Do not smoke. Avoid excessive inhalation of vapors. Use with adequate ventilation. Contains petroleum distillates. If swallowed do not induce vomiting. Call a physician immediately. KEEP OUT OF REACH OF CHILDREN.

First Aid: Skin: Wash exposed area thoroughly with soap and water. Eyes: Flush with large amounts of water, lifting upper and lower lids occasionally. Ingestion: Do not induce vomiting. Call a physician immediately



Capitol USA, LLC
300 Cross Plains Blvd. • PO Box 2023
Dalton, GA 30722
800-831-8381 • Fax: 706-277-5753
Jim Walker ProSeries TechLine 888-234-8400
Website www.capitolusa.com