



product

Specification

WOODY 060

High Performance Acrylic-Urethane Wood Flooring Adhesive



WOODY 060 is a premium performance, high solids, acrylic-urethane latex based formulation designed specifically for the critical demands of wood floor installation. WOODY 060 can be used to install finger block parquet, 3- and

5-ply engineered plank. WOODY 060's smooth troweling formula makes it easy to spread and its excellent early green strength accommodates most tough wood flooring installations.

Description: WOODY060 Acrylic Urethane Wood Flooring Adhesive

Flammability: Non-Flammable

Open Time: 0-15 minutes

Working Time: 45 minutes


Limitations: For interior use only. Protect from freezing.

Packaging: 4 Gallon • 1 Gallon

INSTRUCTIONS FOR USE


1. Condition adhesive and materials to 65°F and 35%-65% relative humidity, 48 hours prior to and after installation.
2. Sweep floor and remove any dirt or debris prior to installation.
3. Make sure floor is free from grease, oil, paint or other contaminant that will interfere with the bond of the adhesive.
4. Spread adhesive with the appropriate trowel
5. Allow adhesive to flash for 15 minutes.
6. Apply only as much adhesive that can be installed within 45 minutes.
7. Inspect every piece for defects prior to placing into the adhesive.
8. Clean up wet adhesive with a white cloth and soap and water. Dried adhesive residue can be removed with mineral spirits.

Trowel Recommendations and Coverage Statements



3/16 x 1/4 x 1/2

50 square feet /gallon
• Engineered Plank (4 inch wide max)
• Prefinished Parquet



1/8 x 1/8 x 1/8

Prefinished Parquet (3/8")
70-80 sq. ft./gal

Roberts Capitol, Inc.
Boca Raton, FL 33487
www.capitoladhesives.com